

according to regulation (EC) No 1907/2006 (REACH) and 1272/2008/EC MOL-LUB Ltd.

Trade name: MOL Farm Protect E9 15W-40 multigrade diesel engine oil

Version: 4 Latest revision: 04. 07. 2018 Date of issue: 20. 01. 2014 Page: 1/(14)

### SECTION 1 Identification of the mixture/substance and of the company/undertaking

1.1 Product identifier:

### MOL Farm Protect E9 15W-40 multigrade diesel engine oil

1.2 Relevant identified uses of the mixture or substance and uses advised against

Relevant identified uses: multigrade diesel motor oil

Uses advised against: no data

1.3 Details of the supplier of the safety data sheet:

MOL-LUB Lubricant Production Trade and Service Limited Liability Company

H-2931 Almásfüzitő, Fő út 21., Hungary

Phone / Fax: +36 34 526 330 / +36 34 526 391

E-mail: kenoanyag@mol.hu

Request SDS of:

MOL-LUB Lubricant Production Trade and Service Limited Liability Company

**Customer Service Center** 

H-2931 Almásfüzitő, Fő út 21., Hungary

Phone / Fax: +36 80 201 296 / +36 34 348 010

Responsible for SDS:

MOL-LUB Ltd. Csaba Horváth, head of SD, HSE & Business Support

Phone: +36 34 526 343; Mobile: +36 20 474 2644

E-mail: csahorvath@mol.hu

1.4 Emergency telephone number

Emergency telephone (07-15<sup>20</sup> h): +36 34 526 210 (CET) on workdays

Health Toxicological Information Service (ETTSZ 1096 Budapest, Nagyvárad tér 2.)

Tel.: 36 80 201 199 (0-24 h, free number).

National Health Toxicological Information Service

#### **SECTION 2** Hazards identification

2.1 Classification of the <u>mixture</u> or substance

Hazard Class and Category: Hazard statement:

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting

effects.





Trade name: MOL Farm Protect E9 15W-40 multigrade diesel engine oil

Version: 4 Latest revision: 04. 07. 2018 Date of issue: 20. 01. 2014 Page: 2/(14)

2.2 Label elements

Product identification: Trade name: MOL Farm Protect E9 15W-40 multigrade diesel

engine oil

Hazardous component(s): -

GHS Pictogram: not required signal word: not required

Hazard statement:

**H412** Harmful to aquatic life with long lasting effects.

Supplemental hazard information:

**EUH 208** Contains Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium

salts and Benzene, polypropene derivatives, sulfonated, calcium

salts. May produce an allergic reaction

Precautionary statements – General: -

Precautionary statements – Prevention:

**P273** Avoid release to the environment.

Precautionary statements – Response: -

Precautionary statements - Storage: -

Precautionary statements – Disposal:

**P501** Dispose of contents/container in accordance with national regulation.

Other liabilities for labelling:

Tactile warning of danger: Not required.

Transport classification: see section 14.

2.3 Other hazards

The product does not contain any PBT or vPvB substance according to annex XIII of regulation (EC) 1907/2006.





Trade name: MOL Farm Protect E9 15W-40 multigrade diesel engine oil

Version: 4 Latest revision: 04. 07. 2018 Date of issue: 20. 01. 2014 Page: 3/(14)

## **SECTION 3** Composition/information on ingredients

3.2 Mixtures

Chemical description: Mixture of refined mineral base oils containing additives.

Component(s) / Hazardous component(s):

Nama	EU	CAS	Hazard classes and	Hazard	Conc.
Name	number	number	cat.	statements	%(m/m)
Base oil – unspecified,	265-157-1	64742-54-7	=	-	max. 70
hydrotreated heavy			(Note L)		
paraffinic, C20-C50*					
REACH Registr. Nr.:					
01-2119484627-25					
Base oil – unspecified,	265-157-1	64742-54-7	Asp. Tox. 1	H304	max. 20
hydrotreated heavy			(Note L)		
paraffinic, C20-C50*					
REACH Registr. Nr.:					
01-2119484627-25					
Base oil mixture *,**			Asp. Tox. 1	H304	max. 8.0
			(Note L)		
Lubricating oils	309-877-7	101316-72-7	-	-	max. 5
(petroleum), C24-C50*			(L megjegyzés)		
REACH Registr. Nr.:					
01-2119489969-06					
Reaction products of	253-249-4	36878-20-3	Aquatic Chronic 4	H413	max. 4.0
Benzeneamine, N-phenyl-					
with nonene (branched)					
REACH Registr. Nr.:					
01-2119488911-28					
Zinc alkyl	283-392-8	84605-29-8	Skin Irrit. 2	H315	max. 1.5
dithiophospate***			Eye Dam. 1	H318	
REACH Registr. Nr.:			Aquatic Chronic 2	H411	
01-2119493626-26					
Benzenesulfonic acid,	274-263-7	70024-69-0	Skin Sens. 1B.	H317	max. 0.8
mono-C16-24-alkyl					
derivs., calcium salts					
REACH Registr. Nr.:					
01-2119492616-28					
Benzene, polypropene	616-278-7	75975-85-8	Skin Sens. 1B.	H317	max. 0.2
derivatives, sulfonated,					
calcium salts					
				<u> </u>	1



according to regulation (EC) No 1907/2006 (REACH) and 1272/2008/EC MOL-LUB Ltd.

MOL Farm Protect E9 15W-40 multigrade diesel engine oil Trade name:

Version: 4 Latest revision: 04, 07, 2018 Date of issue: 20. 01. 2014 Page: 4/(14)

Name	EU	CAS	Hazard classes and	Hazard	Conc.
Name	number	number	cat.	statements	%(m/m)
Phenol, dodecyl-branched	310-154-3	121158-58-5	Skin Corr. 1C	H314	max. 0.05
REACH Registr. Nr.:			Eye Dam. 1	H318	
01-2119513207-49			Repr. 1B	H360F	
			Aquatic Acute1	H400 (M=10)	
			Aquatic Chronic 1	H410 (M=10)	

<sup>\*:</sup> with exposure limit

\*\* Includes one or more of the following:

EU number: 265-157-1, REACH Registr. Nr.: 01-2119484627-25,

EU number: 265-169-7, REACH Registr. Nr.:01-2119471299-27,

EU number: 265-158-7, REACH Registr. Nr.:01-2119487077-29,

EU number: 265-159-2, REACH Registr. Nr.:01-2119480132-48

\*\*\* Specific concentration limit:

Skin Irrit. 2: 6.25 % < C < 100 %; Eve Irrit. 2: 10 % < C < 12.5 %;

Eye Dam. 1: 12.5 % < C  $\le$  100 %

The full text of each relevant H- phrase and Hazard classes and cat. see in Section 16.

#### SECTION 4 First aid measures

Description of first aid measures

General information: Never give anything by mouth to an unconscious person, or never

induce vomiting.

Inhalation: Remove the affected person to fresh air. If rapid recovery does not occur, obtain

medical attention.

Skin contact: Remove contaminated clothing. Wash skin with large amounts of water, use

soap. In case of persistent irritation, get medical attention.

Flush eyes with plenty of water for 10-15 minutes. In case of persistent Eye contact:

irritation, get medical attention.

If swallowed, give water. Do not induce vomiting. Get medical attention. Ingestion:

Protection of first-aid person: No individual specifications.

Most important symptoms and effects, both acute and delayed 4.2

Prolonged and/or repeated contact may cause irritation on skin or in eyes depending on

individual sensitivity.

May produce an allergic reaction.

4.3 Indication of any immediate medical attention and special treatment need Not required.



according to regulation (EC) No 1907/2006 (REACH) and 1272/2008/EC MOL-LUB Ltd.

Trade name: MOL Farm Protect E9 15W-40 multigrade diesel engine oil

Version: 4 Latest revision: 04. 07. 2018 Date of issue: 20. 01. 2014 Page: 5/(14)

### **SECTION 5** Fire-fighting measures

Fire hazards:

Combustible

5.1 Extinguishing media

Suitable extinguishing media:

Foam, carbon dioxide, dry chemical powder.

Unsuitable extinguishing media:

Water jet.

5.2 Special hazards arising from the mixture or substance

Hazardous combustion products:

On burning, carbon monoxide, carbon dioxide, sulphur oxides, phosphor oxide, zinc-oxide, various hydrocarbons and soot can be formed.

5.3 Advice for fire-fighters

Special protective equipment:

According to the existing fire-fighting regulations. Respiratory protection.

#### Further information:

Collect contaminated fire fighting water separately. It must not enter the sewage system. Contaminated extinguishing water must be disposed of in accordance with official regulations.

#### **SECTION 6** Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions: see Section 8.

Danger of slipping on leaked out/spilled product.

6.2 Environmental precautions:

Confine spills to prevent material from entering sewers, watercourses, drains and into soil Notify relevant authority.





Trade name: MOL Farm Protect E9 15W-40 multigrade diesel engine oil

Version: 4 Latest revision: 04. 07. 2018 Date of issue: 20. 01. 2014 Page: 6/(14)

6.3 Methods and material for containment and cleaning up

On soil: All kind of ignition sources should be remove. Recover free liquid by

pumping. Contain the rest or small quantities with sand, earth or other

suitable absorbents. Dispose of according to local regulations.

On water: Confine the spillage. Remove from surface by skimming or suitable

absorbents. Notify local authorities according to regulations.

6.4 Reference to other sections

Personal precautions: see section 8.

Waste treatment methods: see section 13.

### **SECTION 7** Handling and storage

7.1 Precautions for safe handling

Keep general measures applied for normal operations with lubricants and flammable liquids. Keep away from radiant heat and open flame.

Avoid contact with skin and eyes. Avoid prolonged breathing of oil vapours or mists.

Ensure washing facilities after working hours and before breaks. Take off contaminated or oil-soaked clothing, wash with warm water and soap.

When using do not eat, drink or smoke. Avoid splashing the product.

Handling temperature: not known

7.2 Conditions for safe storage, including any incompatibilities

Storage facilities must comply with regulations for storing of flammable liquids.

Store in dry, well ventilated place in original, closed containers.

Keep away from radiant heat, open flame and strong oxidizing agents.

Storage temperature: max. 40°C

7.3 Specific end use(s)

Multigrade diesel motor oil.

### **SECTION 8** Exposure controls / personal protection

Engineering control measures:

Not required.



according to regulation (EC) No 1907/2006 (REACH) and 1272/2008/EC MOL-LUB Ltd.

Trade name: MOL Farm Protect E9 15W-40 multigrade diesel engine oil

Version: 4 Latest revision: 04. 07. 2018 Date of issue: 20. 01. 2014 Page: 7/(14)

8.1 Control parameters:

Mineral oil mist: TWA: 5 mg/m<sup>3</sup>; STEL: 10 mg/m<sup>3</sup>, for oil mist, vapour excluded

(ACGIH).

Method of testing, recommended: NIOSH 5026

8.2 Exposure controls

Personal protection:

Respiratory protection: Under normal conditions not required. In case of exceeded

exposure-limits respiratory protection with particle-filter is

recommended.

Hand protection: Oil resistant gloves (EN 374, Breakthrough time 480 min) (e.g.

nitrile rubber – minimal thickness 0.33 mm).

Note: Manufacturer's directions for use and the conditions of

application should be observed.

Eye protection: Where splashing is possible, wear safety glasses (EN 166).

Skin protection: Protective clothing (oil resistant).

Other special: No data.

Environmental exposure controls:

Do not discharge into drains/surface waters/groundwater.

### **SECTION 9** Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance:

Physical state: liquid

Colour: brown, bright, clear

Odour: characteristic

Change in physical state:

Pour point (ISO 3016): typ. -39°C Boiling point (DIN 51356): not available

Others:

Flash point (COC) (EN ISO 2592): typ. 230°C Ignition point (EN ISO 2592): not available Autoignition temperature: not available Explosive properties: not explosive Oxidizing properties: not oxidize Vapour pressure at 20°C: negligible



according to regulation (EC) No 1907/2006 (REACH) and 1272/2008/EC MOL-LUB Ltd.

Trade name: MOL Farm Protect E9 15W-40 multigrade diesel engine oil

Version: 4 Latest revision: 04. 07. 2018 Date of issue: 20. 01. 2014 Page: 8/(14)

Density at  $15^{\circ}$ C (EN ISO 12185):  $0.865 - 0.885 \text{ g/cm}^3$ 

Solubility in water: practically insoluble in water

Solubility in other solvents: gasoline, kerosene, toluene, etc. n-Octanol/water partition coefficient: not available

n-Octanol/water partition coefficient:

Vapour density:

Heating value:

Kinematic viscosity at 40°C (EN ISO 3104):

Kinematic viscosity at 100°C (EN ISO 3104):

typ. 108.7 mm²/s

typ. 14.4 mm²/s

pH: typ. 14.4 min /s

9.2 Other information

no data available

## **SECTION 10** Stability and reactivity

10.1 Reactivity: Dangerous reactivity not known.

10.2 Chemical stability: No decomposition if stored and handled properly.

10.3 Possibility of hazardous

reactions: Not known.

10.4 Conditions to avoid: Direct heat or ignition sources.

10.5 Incompatible materials: Strong oxidizing agents.

10.6 Hazardous decomposition No dangerous decomposition products are formed under normal

products: conditions. Hazardous combustion products: See Section 5.

### **SECTION 11** Toxicological information

11.1 Information on toxicological effects

Acute toxicity:

Oral:  $LD_{50}$  (rat) > 2000 mg/kg (based on components) Dermal:  $LD_{50}$  (rabbit) > 2000 mg/kg (based on components)

Acute toxicity: irritation

Skin: not irritant (based on components)

Eye: not irritant (based on components).

Respiratory or skin sensitisation: not sensitising (based on components), but may produce

an allergic reaction





Trade name: MOL Farm Protect E9 15W-40 multigrade diesel engine oil

Version: 4 Latest revision: 04. 07. 2018 Date of issue: 20. 01. 2014 Page: 9/(14)

#### Other information, specific effects:

Note L: The classification as a carcinogen need not apply according to 1272/2008/EC, because it can be shown that the substance contains less than 3 % DMSO extract as measured by IP 346.

Germ cell mutagenicity: not known, resp. not mutagen (based on components)
Carcinogenicity: not known, resp. not carcinogen (based on components)
Reproductive toxicity: not known, resp. no reproduction-damaging effect

(based on components)

STOT-single exposure: not classified STOT-repeated exposure: not classified Aspiration hazard: not classified

### **SECTION 12** Ecological information

12.1 Toxicity No data for the product.

Aquatic organisms: Soil organisms:

Plants:

12.2 Persistence and degradability No data available. Biodegradability: No data available.

12.3 Bioaccumulative potential No data available.

12.4 Mobility

Mobility in soil Absorbs in soil. Mobility in water: Floats on water.

12.5 Results of PBT and vPvB

assessment Does not contain PBT and vPvB substances.

12.6 Other adverse effects

Heavy metal content: None.

PCT, PCB and other chlorinated

hydrocarbons: None.

Environmental effects: Harmful to aquatic life with long lasting effects.

Water hazard class (German): WGK 2 (Classification by VwVwS)



according to regulation (EC) No 1907/2006 (REACH) and 1272/2008/EC MOL-LUB Ltd.

Trade name: MOL Farm Protect E9 15W-40 multigrade diesel engine oil

Version: 4 Latest revision: 04. 07. 2018 Date of issue: 20. 01. 2014 Page: 10/(14)

### **SECTION 13** Disposal considerations

#### 13.1 Waste treatment methods

Product disposal:

Wastes of the product or used oil should be treated as hazardous waste.

Waste Identification Code: 13 02 05\*

Mineral-based non-chlorinated engine, gear and lubricating oils.

Disposal must be in compliance with national and local regulations.

Recommended waste treatment method: incineration

### Packaging disposal:

Containers with product residue should also be treated as hazardous waste according to national and local disposal regulations.

Waste Identification Code: 15 01 10\*

Packaging containing residues of or contaminated by dangerous substances.

Disposal must be in compliance with national and local regulations.

#### Wastewater:

Quality of wastewater emitted to natural water must comply with national and local regulations.

Care should be taken in any case to ensure compliance with EC, national and local regulations. It is the responsibility of the user to know all relevant national and local regulations.

### **SECTION 14** Transport information

Land transport:

Road/ Railway ADR/RID: Not classified.

14.1. not classified UN number: 14.2. UN proper shipping name: not classified 14.3. Transport hazard class(es): not classified 14.4. Packing group: not classified Environmental hazards: 14.5. not classified 14.6. Special precautions for user: not classified

Waterways:

Inland waterways/ Sea transport ADN/IMDG: Not apply to the product.

Air transport: ICAO / IATA: Not apply to the product.



according to regulation (EC) No 1907/2006 (REACH) and 1272/2008/EC MOL-LUB Ltd.

Trade name: MOL Farm Protect E9 15W-40 multigrade diesel engine oil

Version: 4 Latest revision: 04. 07. 2018 Date of issue: 20. 01. 2014 Page: 11/(14)

### **SECTION 15** Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the mixture. This safety data sheet has been prepared according to Regulation (EC) No 1907/2006 (mod.: 2015/830/EU) and to Regulation (EC) 1272/2008.

15.2 Chemical safety assessment.

#### **SECTION 16** Other information

The information given in this data sheet is based on our best knowledge at the time of publication. The information is related only to this product and is intended to assist its safe transport, handling and use. The given physical and chemical parameters describe the product only for the purpose of safety requirements and therefore should not be construed as guaranteeing any specific property of the product or as being part of a product specification or any contract.

The manufacturer or supplier shall not take responsibility for any damages from the use other than recommended or other misuse of the product. It is the responsibility of the user to keep regulatory precautions and observe recommendations for safe use of the product.

Source of data presented in this material safety data sheet:

Test results of this product Material safety data sheets of product's components 1272/2008/EC regulation, Annex XVII. of REACH Relevant Hungarian regulation and EU directives

Classification for mixtures and used evaluation method according to regulation 1272/2008/EC (CLP)

Aquatic Chronic 3 H412 calculation method



according to regulation (EC) No 1907/2006 (REACH) and 1272/2008/EC MOL-LUB Ltd.

Trade name: MOL Farm Protect E9 15W-40 multigrade diesel engine oil

Version: 4 Latest revision: 04. 07. 2018 Date of issue: 20. 01. 2014 Page: 12/(14)

The full text of each relevant H- phrase and Hazard classes and cat. in Section 3.:

H304 May be fatal if swallowed and enters airways. H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage. H360F May damage fertility. H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.
 H411 Toxic to aquatic life with long lasting effects.
 H412 Harmful to aquatic life with long lasting effects.

Asp.Tox.1 Aspiration hazard Category 1

Skin Corr. 1C Skin corrosion/irritation Category 1C Skin Irrit. 2 Skin corrosion/irritation Category 2

Skin Sens. 1B Respiratory/skin sensitization Category 1B Eye Dam. 1 Serious eye damage/eye irritation Category 1

Repr. 1B. Reproductive toxicity Category 1B.

Aquatic Acute 1 Hazardous to the aquatic environment, Acute Category 1 Hazardous to the aquatic environment, Chronic Category 1 Hazardous to the aquatic environment, Chronic Category 2 Hazardous to the aquatic environment, Chronic Category 3

#### Legend:

ADN European Agreement concerning the International Carriage of Dangerous Goods by Inland

Waterways

ADR European Agreement concerning the International Carriage of Dangerous Goods by Road

ATE Acute Toxicity Estimate
BCF Biocontrentration Factor
BOD Biological Oxigen Demand

Bw Body Weight

C&L Classification and Labeling CAS Chemical Abstracts Service

CLP Classification, Labelling and Packaging

CMR Carcigonic, Mutagenic or toxic to Reproduction

COD Chemical Oxygen Demand CSA Chemical Safety Assessment



according to regulation (EC) No 1907/2006 (REACH) and 1272/2008/EC  $\,$  MOL-LUB  $\,$  Ltd.

Trade name: MOL Farm Protect E9 15W-40 multigrade diesel engine oil

Version: 4 Latest revision: 04. 07. 2018 Date of issue: 20. 01. 2014 Page: 13/(14)

CSR	Chemical Safety Report
DMEL	Derived Minimal Effect Level
DNEL	Derived No Effect Level
ECHA	European Cheamicals Agency
Ecx	Effective Concentration x%
Edx	Effective Dose x%
ELINCS	European List of Notified Chemical Substances
ErC50	EC50 in terms of reduction of growth rate;
ES	Exposure Scenario
ESIS	European Chemical Substances Information System
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LCx	Lethal Concentration x%
LDx	Lethal Dose x%
LOAEC	Lowest Observed Adverse Effect Concentration
LOAEL	Lowest Observed Adverse Effect Level
LOEC	Lowest Observed Effect Concentration
LOEL	Lowest Observed Effect Level
NOEC	No observed effect concentration
NOEL	No observed effect level
NLP	No-Longer Polymer
NOAEL	No Observed Adverse Effect Level
OECD	Organisation for Economic Cooperation and Development
PBT	Persistent Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SVHC	Substance of Very High Concern
UVCB	substance of unknown or variable composition, complex reaction products or biologica materials
VOC	Volatile organic compounds
vPvB	Very Persistent and very Bio-accumulative

### **Revision Indicators:**

Section	Subject of change	Date	Version
1	Details of the supplier of the safety data sheet,	01.10.2015	2
	Responsible for SDS		
3	Composition/information on ingredients		
9	Physical and chemical properties		
1-16	Other corrections, revision modification according to		
	2015/830 /EU		





Trade name: MOL Farm Protect E9 15W-40 multigrade diesel engine oil

Version: 4 Latest revision: 04. 07. 2018 Date of issue: 20. 01. 2014 Page: 14/(14)

Revision Indicators:					
Section	Subject of change	Date	Version		
2	Hazards identification	20.09.2017	3		
3	Composition/information on ingredients				
1-16	Other corrections				
2, 2.2	Hazards identification. Label elements	04.07.2018	4		
3	Composition/information on ingredients				
8	Exposure controls / personal protection				
9	Physical and chemical properties				
11	Toxicological information				
1-16	Other corrections				